

ROOF 60

MW-EN13162-T5-DS(70,90)-CS(10)60-TR15-PL(5)800-WS-WL(P)-MU1

- | | |
|--|---|
| 1. Unique identification code of the product-type: ROOF 60 | 4. Authorized representative: - |
| 2. Intended use: Thermal insulation products for buildings – Factory made mineral wool (MW) products. For uses subject to regulations on reaction to fire A1. | 5. System of attestation of conformity: System 1, System 3 |
| 3. Manufacturer: Joint Stock Company «GomelStroyMaterialy» Republic of Belarus, Mogilevskaya str., 14, 246010 Gomel | 6. Harmonized standard: EN 13162:2012+A1:2015
Notified certification body: No. 1020 performed Certificate of constancy of performance No. 1020 –CPR-010022606
Report of the assessment of performance No. 1020-CPR-010-044681. |

7.Declared Performance

Essential Characteristics	Clauses in this and other European standard(s) related to essential characteristics	Harmonized standard
Reaction to fire	Reaction to fire Euroclasses A1	EN 13162:2012+A1:2015
Release of dangerous substances to the indoor environment	Release of dangerous substances EU level not yet available NPD	
Acoustic absorption index	Sound absorption α_p (A _{Pi}) and α_w (A _{Wi}) declared NPD	
Impact noise transmission index (for floors)	Dynamic stiffness S',S_d declared NPD	
	Thickness, d_t and classes for thickness tolerances T6 or T7 NPD	
	Compressibility c C_{Pi} declared NPD	
	Airflow resistivity A_F declared NPD	
Direct airborne sound insulation index	Airflow resistivity A_F declared NPD	
Continuous glowing combustion	Continuous glowing combustion EU level not yet available NPD	
Thermal resistance	Thermal resistance and thermal conductivity Thermal conductivity λ (W/mK) 0,038 Thermal resistance $R = d/\lambda$ (m ² K/W) 1,05 ÷ 3,95. See table	
	Thickness Thickness range (mm) 40 ÷ 150 T_i class for thickness tolerance T5	
Water permeability	Short term water absorption WS -declared W_p (kg/m ²) WS	
	Long term water absorption WL(P) declared W_{L(P)} (kg/m ²) WL(P)	
Water vapour permeability	Water vapour transmission Declared μ_i (MU _i) or Z_i MU1	
Compressive strength	Compressive stress or compressive strength CS(10)_i or CS(10/Y)_i declared (kPa) CS(10)60	
	Point load PL(5)_i declared (N) PL(5)800	
Durability of reaction to fire against heat, weathering, ageing/degradation	Durability characteristics Euroclasses A1	
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance and thermal conductivity Declared $R = d/\lambda$ (m ² K/W) 1,05 ÷ 3,95. See table Declared λ W/mK 0,038	
	Durability characteristics DS(70,-) declared. The relative changes in thickness NPD DS(70,90) declared. The relative changes in thickness DS(70,90)	
Tensile strength	Tensile strength perpendicular to faces T_{ri} declared (kPa) TR15	
Durability of compressive strength against ageing/degradation	Compressive creep CC(i1/i2) α_c compressive creep declared X_{c1} and X_{c2} NPD	

Thermal resistance RD

d (mm)	40	50	60	70	80	90	100	110	120	130	140	150
R_D m ² K/W	1,05	1,30	1,55	1,80	2,10	2,35	2,60	2,85	3,15	3,40	3,65	3,95

8. The Characteristics of the product specified above correspond to the declared characteristics. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.

13 February 2023
General Director Joint Stock Company «GomelStroyMaterialy»



Stanislav Zheromski

Natural thermal insulation
BELTEP
JSC «GOMELSTROYMATERIALY»

Joint Stock Company «GomelStroyMaterialy»,
Republic of Belarus, Mogilevskaya str., 14, 246010 Gomel
www.oaogsm.by
e-mail: info@gstrmat.by
tel./faks: +375 232 59 51 18