

VENT 25
MW-EN13162-T5-DS(70,90)-CS(10)15-TR7,5-WS-WL(P)-MU1-AF27

- | | |
|---|--|
| <p>1. Unique identification code of the product-type: VENT 25</p> <p>2. Intended use: Thermal insulation products for buildings – Factory made mineral wool (MW) products. For uses subject to regulations on reaction to fire A1.</p> <p>3. Manufacturer: Joint Stock Company «GomelStroyMaterialy» Republic of Belarus, 246010, Mogilevskaya str., 14, Gomel</p> | <p>4. Authorized representative: -</p> <p>5. System of attestation of conformity: System 1, System 3</p> <p>6. Harmonized standard: EN 13162:2012+A1:2015
 Notified certification body: No. 1020 performed Certificate of constancy of performance No. 1020 –CPR-010022606
 Report of the assessment of performance No. 1020-CPR-010-044681.</p> |
|---|--|

7. Declared Performance

Essential Characteristics	Clauses in this and other European standard(s) related to essential characteristics	Harmonized standard
Reaction to fire	Reaction to fire Euroclasses A1	EN 13162:2012+A1:2015
Release of dangerous substances to the indoor environment	Release of dangerous substances EU level not yet available NPD	
Acoustic absorption index	Sound absorption α_p (APi) and a_w (AWi) declared NPD	
Impact noise transmission index (for floors)	Dynamic stiffness s' SD deklarowane NPD	
	Thickness, d_L d_L and classes for thickness tolerances T6 lor T7 NPD	
	Compressibility c CPI declared NPD	
	Airflow resistivity AFr i declared AF27	
Direct airborne sound insulation index	Airflow resistivity AFr i declared AF27	
Continuous glowing combustion	Continuous glowing combustion EU level not yet available NPD	
Thermal resistance	Thermal resistance and thermal conductivity Thermal conductivity λ (W/mK) 0,035 Thermal resistance $R = d / \lambda$ (m ² K/W) 0,85+5,70 . See tabel	
	Thickness Thickness range (mm) 30 – 200 Ti class for thickness tolerance T5	
Water permeability	Short term water absorption WS declared WP; kg/m ² WS	
	Long term water absorption WL(P) - declared W IP;kg/m ² WL(P)	
Water vapour permeability	Water vapour transmission Declared μ_i ; (MU _i) or Z _i MU1	
Compressive strength	Compressive stress or compressive strength CS(10) _i or CS(10/Y) _i declared (kPa) CS(10)15	
	Point load PL(5) _i declared (N) NPD	
Durability of reaction to fire against heat, weathering, ageing\degradation	Durability characteristics Euroclasses A1	
Durability of thermal resistance against heat, weathering, ageing\degradation	Thermal resistance and thermal conductivity Declared $R = d / \lambda$ m ² K/W 0,85+5,70 . See tabel Declared λ W/mK 0,035	
	Durability characteristics DS(70) declared. The relative changes in thickness NPD DS(70,90) declared. The relative changes in thickness DS(70,90)	
Tensile strength	Tensile strength perpendicular to faces TR _i declared (kPa) TR7,5	
Durability of c ompressive strength against ageing\degradation	Compressive creep CC(i1/i2) _c compressive creep declared X_{ct} and X_t NPD	

Thermal resistance R_D

d (mm)	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200
R _D m ² K/W	0,85	1,10	1,40	1,70	2,00	2,25	2,55	2,85	3,10	3,40	3,70	4,00	4,25	4,55	4,85	5,10	5,40	5,70

8. The Characteristics of the product specified above correspond to the declared characteristics. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.

13 February 2023
General Director Joint Stock Company «GomelStroyMaterialy»



Stanislav Zheromski

Natural thermal insulation

BELTEP
JSC «GOMELSTROYMATERIALY»

Joint Stock Company «GomelStroyMaterialy»,
Republic of Belarus, Mogilevskaya str., 14, 246010 Gomel
www.oaogsm.by
e-mail: info@gstrmat.by
tel./faks: +375 232 59 51 18